

## HST LINE

HST 54x39 S a standard horizontal fireplace insert with output of 5.9kW

HST 54x39 S a standard horizontal fireplace insert with output of 7.6kW

HST 54x39 S a standard horizontal fireplace insert with output of 9.3 kW

## HST FIREPLACE INSERT INVENTORY:

- Fireplace front cover – black
- Ceramic insert
- Integrated 4-degree throttle
- Regulated cast iron flue
- Decor glass
- Double height adjustment

## HST FIREPLACE INSERT QUALITIES

1. **Cast iron flue** that is 360°-regulated allows to evacuate waste in any direction.
2. **Clean glass system** – optimal air circulation reduces glass sooting.
3. **Low fireplace insert depth** allows for shallow installation.
4. **Decor glass** included provides an attractive exposure of fire.
5. **Steel door** made of reinforced profile ensures rigidity and endurance.
6. **Combustion chamber** coated with a special concrete that accumulates warmth, fire-resistant up to 1000°C.
7. **Integrated 4-degree throttle** regulates primary and secondary air transfer.
8. **Selectable height control** allows to adjust fireplace insert height to the installation spot.
9. **Adjustable stands** ensure smooth height control up to 40mm.
10. **Grateless hearth** allows the so-called afterburning on ash.

<b>SPECS</b>	<b>HST 54 X 39 S</b>	<b>HST 59 X 43 S</b>	<b>HST 68 X 43 S</b>
Nominal power (kW)	5,9	7,6	9,3
Flue diameter (mm)	160	160	160
Material (mm)	boiler steel 4		
Type of fuelnon	coniferous wood, briquette, brown coal		
Glass dimensions in the insert (mm)	545 x 390	590 x 430	680 x 430
External width (mm)	656	701	791
Intake diameter (mm)	125	125	125
Insert height with flue (mm)	1273	1313	1313
Insert height without flue (mm)	1020	1060	1060
Insert depth (mm)	330	330	330